

**eko
okna**



SALAMANDER

PVC WINDOW AND DOOR SYSTEMS

STREAMLINE 76

WINDOW AND DOOR SYSTEM



A perfect choice for those who value comfort and elegance. Windows based on Streamline 76 combine top safety parameters with great thermal and acoustic insulation. Resistant to external factors and characterised by their intense white colour.

- B class profiles,
- 5-chamber structure,
- installation depth: 76 mm,
- standard device preventing an incorrect handle position (T&T windows),
- standard microventilation in a corner (T&T windows),
- standard hardware is equipped with 6 anti-burglary bolts per sash,
- equipped with 2 gaskets,
- open steel (1.5 mm thick) as a standard,
- manufactured using white, brown, and caramel core,
- available with a Classic-line or Round-line,
- glazing with glass packages up to 49 mm width,
- standard glazing package 4/16Ar/4th [Ug=1,1]*,
- aluminium covers can be used,
- renovation windows are available,
- concealed hardware can be used.

*Standard of the day 16.04.2019.
Requires technological confirmation.

5

chamber structure

2

gaskets system

76

installation depth
[mm]

A

aluminium covers

R

Renovation

0,97

Uw for Ug=0.7
(warm edge)

COLOURS

 SAL 02	 SAL 03	 SAL 11	 SAL 18	 SAL 19	 SAL 21
 SAL 25	 SAL 26	 SAL 27	 SAL 33	 SAL 37	 SAL 39
 SAL 41	 SAL 43	 SAL 50	 SAL 51	 SAL 52	 SAL 59
 SAL 60	 SAL 61	 SAL 62	 SAL 67	 SAL 69	 SAL 70
 SAL 71	 SAL 72	 SAL 73	 SAL 74	 SAL 78	 SAL 84
 SAL 87	 SAL 88	 SAL 90	 SAL 91	 SAL 92	 SAL 93
 SAL 107	 SAL 108	 SAL 109	 SAL 110	 SAL 111	 SAL 112
 SAL 113	 SAL 115	 SAL 116			



The publication does not constitute a commercial offer. It is not a basis for submitting complaints. Presented photographs are illustrative pictures, not actual product photos.

